

**VALTORC**

WWW.VALTORC.COM  
AJBENTAL@VALTORC.COM  
1 (866) VALTORC

# BRASS SOLENOID VALVE

## SERIES 810



## BRASS SOLENOID VALVE SERIES 810

2-way, internally piloted, normally closed solenoid valve

**1/4"-1/2"**

Pipe Sizes

**8W, 12W, 14W**

Coils

**2-300 psig**

Operating Pressure



### Materials of Construction

Body:	Brass
Armature Tube:	Stainless Steel 300
Fixed Core:	Stainless Steel 400
Plunger:	Stainless Steel 400
Spring:	Stainless Steel 300
Shading Ring:	Copper

### Electrical Connection

Rating:	NEMA 4
Strain Relief Connector:	Model 09
1/2" Conduit Connector:	Model 01
6 ft. Power Cord:	Model 10

**BUNA**  
Sealing Material**14° - 280° F**  
Temperature Range**Air, Inert gas, Water, Synthetic oils**  
Medium Examples

Model #	Pipe Size (Inch)	Orifice Size (Inch)	Flow Factor (CV)	Watt Rating (W)	Min. Pressure (PSI)	Max. Pressure (AC/DC)
810-A	1/4"	7/16"	1.50	8	2	300/150
810-B	1/4"	7/16"	1.50	12	2	300/300
810-C	1/4"	7/16"	1.50	14	2	300/300
810-D	3/8"	7/16"	1.70	8	2	300/150
810-E	3/8"	7/16"	1.70	12	2	300/300
810-F	3/8"	7/16"	1.70	14	2	300/300
810-G	1/2"	7/16"	1.70	8	2	300/150
810-H	1/2"	7/16"	1.70	12	2	300/300
810-I	1/2"	7/16"	1.70	14	2	300/300

**VITON**  
Sealing Material**14° - 195° F**  
Temperature Range**Air, Inert gas, Water**  
Medium Examples

Model #	Pipe Size (Inch)	Orifice Size (Inch)	Flow Factor (CV)	Watt Rating (W)	Min. Pressure (PSI)	Max. Pressure (AC/DC)
810-A	1/4"	7/16"	1.50	8	2	300/150
810-B	1/4"	7/16"	1.50	12	2	300/300
810-C	1/4"	7/16"	1.50	14	2	300/300
810-D	3/8"	7/16"	1.70	8	2	300/150
810-E	3/8"	7/16"	1.70	12	2	300/300
810-F	3/8"	7/16"	1.70	14	2	300/300
810-G	1/2"	7/16"	1.70	8	2	300/150
810-H	1/2"	7/16"	1.70	12	2	300/300
810-I	1/2"	7/16"	1.70	14	2	300/300